




Technical specifications

Cane & Sand

References CEA...

Composition: 100% cane on paper backing
Weight: $\pm 280 \text{ g/m}^2$ ($\pm 7,5 \text{ oz/sq yd}$)



Width of the wallcovering is 91 cm (35" 4/5).



Pattern repeat is 0 cm (0") and the design does not need matching.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, abundantly humidify the backing of the wallcovering, soaking time at least 20 minutes.




Ecological



Moderate light resistance




Fire resistant: US (class A), FR (M1)



Sold by cut length

References SDA1...

Composition: mixture of cellulose and polyester
Weight: $\pm 205 \text{ g/m}^2$ ($\pm 5,49 \text{ oz/sq yd}$)
Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat is 0 cm (0") and the design does not need to be matched.



This design needs reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Extra-washable.




Ecological.



Light resistance: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1)



Sold by cut length.