



Technical specifications


Oxygen

References O21..

Composition: mixture of cellulose and polyester

Weight: $\pm 197 \text{ g/m}^2$ ($\pm 5,8 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat of the design is 50,7 cm (20") and needs a straight match.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable




Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.

References O22..

Composition: mixture of cellulose and polyester

Weight: $\pm 197 \text{ g/m}^2$ ($\pm 5,8 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat of the design is 64 cm (25" 1/5) and does not need to be matched.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.



References O23..

Composition: glass beads on non-woven backing

Weight: $\pm 304 \text{ g/m}^2$ ($\pm 8,9 \text{ oz/sq yd}$)



Width of the wallcovering is 92 cm (36" 1/5)



Pattern repeat of the design is 0 cm (0") and does not need to be matched.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Washable



Ecological



Light fastness: Xeno test 6-7



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.

References O24..

Composition: mixture of cellulose and polyester

Weight: $\pm 197 \text{ g/m}^2$ ($\pm 5,8 \text{ oz/sq yd}$)

Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat of the design is 32 cm (12" 3/5) and needs a straight match.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.




References O25..

Composition: mixture of cellulose and polyester with sisal fibres

Weight: $\pm 197 \text{ g/m}^2$ ($\pm 5,8 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).



Pattern repeat of the design is 0 cm (0") and does not need to be matched.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.

References O26..

Composition: mixture of cellulose and polyester

Weight: $\pm 197 \text{ g/m}^2$ ($\pm 5,8 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat of the design is 64 cm (25" 1/5) and needs a straight match.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.