



Technical specifications

Silver & Gold


References SGA0.. & SGA1..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

The wallcovering can be installed horizontally or vertically.

Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat is 0 cm (0") and the design does not need matching.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable




Ecological



Light resistant:
Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.

References SGA2..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat is 0 cm (0") and the design does not need matching.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable




Ecological



Light resistant:
Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.




References SGA3..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

Custom colouring on request



Width of the wallcovering is 100 cm (39" 1/3).




Pattern repeat is 1,5 cm (0" 3/5) and the design needs a straight match.



This design requires reverse hanging.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable




Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.

References SGA4..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).



Pattern repeat is 32 cm (12" 3/5) and the design needs a straight match.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.




References SGA5..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).



Pattern repeat is 64 cm (25" 1/5) and the design needs a straight match.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).




Sold by cut length.

References SGA6..

Composition: mixture of cellulose and polyester

Weight: $\pm 174 \text{ g/m}^2$ ($\pm 5,1 \text{ oz/sq yd}$)

Custom colouring on request




Width of the wallcovering is 100 cm (39" 1/3).



Pattern repeat is 64 cm (25" 1/5) and the design needs a straight match.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Product complying with the Council Directive 96/98/EC on Marine Equipment.



Washable



Ecological



Light resistant: Xeno test 6-7.



Fire resistant: EU (B S1 D0), UK (class O), US (class A), FR (M1), I (class 1).



Sold by cut length.